



A Precision 1 1/4" Nom. Swage Press for the production of hose assemblies of all types.

Designed specifically for high production work with rapid operation with a large reservoir for continuous use. The press is of a design with a large aperture enabling

optional Die Sets to 2" hose of light construction. The Die Sets used are those of a popular European "Pin" design.

1" 4 Wire Hydraulic Hose Capability

2" 2 Wire Hydraulic Hose Capability

Dies with Colour Coding

Large Aperture

400 VAC 3 Phase Supply

Automatic Motor Control

Standard swaging range 16 to 55mm diam. Extended swaging range 6.5 to 74mm diam.

UL and CE approvals

Dynamic:

Nom. Size (Hydraulic Hose Size Inches)	1 1/4
Die Set Size (mm nom.)	32-XX
Swaging Range (mm with Std. Die Set)	16 to 55
(mm with Optional Dies)	7 to 74
Max. Die Set Opening (mm + Die Set Size)	25
Radial Swaging Force (kN)	1500
Cycle Speed (Full Stroke-Complete Cycle sec.)	12

Physical:

Dimensions (Plan mm x mm x Height mm	1)
	600 x 420 x 540
Weight (Without Dies & Oil kg)	
Shipping Space (m x m x m)	
Shipping Weight (kg)	170
Crate Size (Plan m x m x Height m)0	.72 x 0.55 x 0.78


Electrical:

Supply (Volts / Amps)	400 / 8
Phase (No.)	3
Power (kW)	
Electric Motor Speed (RPM @ 50 Hz)	
Control Power (Volts)	


Hydraulic:

Rated Pressure (bar)	300
Pump Flowrate (l/min)(No Load)	6.7
Reservoir Capacity (litres)	40
Filtration (um).	

Installation:



Specifications May Change Without Notice All Dimensions in Millimeters






Options:

CS32SDS Standard Die Set

8 Die Sets supplied as a package to allow infinite swaging between 16 to 55mm finished swage size. Each Die Set is supplied in a container that will provide for automatic charging of the CS32QCT Quick Change.


32- Extended Range & Special Profile

The Extended Range of	Die Sets Available are as follows:	
32-6.5	6.5 to 8mm finished swage.	
32-8	8 to 10mm finished swage.	
32-10	10 to 12mm finished swage.	
32-12	12 to 14mm finished swage.	
32-14	14 to 16mm finished swage.	
32-53	53 to 60mm finished swage.	
	60 to 67mm finished swage.	
	67 to 74mm finished swage.	
or consult your Dealer for special profile.		




CS32QCT Quick Change Tool

The Quick Change Tool provides for changing of the Dies in a full arrangement on a loaded magnetic tool. The Swage Press is equipped with a Over-Ride Button. that allows free movement of the head to facilitate the installation and removal of the die sets.




CSFP Foot Pedal

The Foot Pedal allows the operator to have his hands free while operating the press. It also provides for the press to go into "Fully Automatic" mode with Auto Retract to a specified Open Diameter set on the control panel. Provides for fast/repetitive operation.



CS132DS Depth Stop


The Depth Stop provides Quick Exact positioning of the hose assembly. Excellent for high volume/repetitive work. It has a Pneumatic Spring which allows for length growth during the swaging process without damage to the coupling



CS32QCR Quick Change Rack

The CS32QCR Quick Change Rack can be mounted against the wall or bolted into the CS32-CAPRI Height Adjustable Stand. It has 11 rosettes in which to stock your 32 Type Die Sets as well as a position to locate the CS32QCT Quick Change Tool.

1 x CS32QCT Quick Change Tool included.



CS-CAPRI Height Adjustable Stand

The CS-CAPRI Height Adjustable Stand allows the Swage Press to be mounted at the most ergonomic height in relation to operator height. The Stand also accepts the CS32QCR Quick Change Rack and CS32QCT Quick Change Tool to complete the package. A Shelving Unit is also supplied to store various items.



Adelaide 08 8228 2411 • Sydney 02 8814 2100 Newcastle 02 4964 2123 • Brisbane 07 3022 3700 • Emerald 07 4988 1800 Mackay 07 4952 4056 • Melbourne 03 8793 6400 Laverton 03 9371 9000 • Perth 08 6216 4600 • Tasmania 03 6427 0908