

### DH Series = Cetop 3

### DK Series = Cetop 5

Manually Operated Spool Valves

4 way, 2 or 3 positions.

MWP on P.A.B. = 350 bar

MWP on T = 160 bar

Flow rates are based on a 10 bar pressure drop using oil to ISO VG 46 at 50°C



CIRCUIT	SPOOL CONTROL	CROSS OVER	Cetop 3 Part No.	nom. l/min	Cetop 5 Part No.	nom. l/min
	SPRING OFFSET	OPEN	<b>DH-0130</b>	35	<b>DK-1130</b>	85
	SPRING OFFSET	CLOSED	<b>DH-0131</b>	25	<b>DK-1131</b>	85
	SPRING CENTRED	N/A	<b>DH-0110</b>	35	<b>DK-1110</b>	85
	SPRING CENTRED	N/A	<b>DH-0111</b>	25	<b>DK-1111</b>	85
	SPRING CENTRED	N/A	<b>DH-0113</b>	25	<b>DK-1113</b>	85
	SPRING CENTRED	N/A	<b>DH-0114</b>	20	<b>DK-1114</b>	80
	3 POS. DETENT	N/A	<b>DH-0140</b>	35	<b>DK-1140</b>	85
	3 POS. DETENT	N/A	<b>DH-0141</b>	25	<b>DK-1141</b>	85
	3 POS. DETENT	N/A	<b>DH-0143</b>	25	<b>DK-1143</b>	85
	3 POS. DETENT	N/A	<b>DH-0144</b>	20	<b>DK-1144</b>	80

<b>DH Series:</b> <u>CAM OPERATED</u> 4 way - 2 pos	CIRCUIT	Part No.	SPOOL CONTROL	PRESSURE (BAR)		Nom. Flow Ltr/Min
				P.A.B.	T	
		<b>DH-0281</b>	SPRING OFFSET	350	120	25

<b>DH Series:</b> <u>OIL PILOT</u>	CIRCUIT	Part No.	SPOOL CONTROL	PRESSURE (BAR)		Nom. Flow Ltr/Min
				P.A.B.	T	
		<b>DH-0510</b>	SPRING CENTRED	350	120	35
		<b>DH-0511</b>	SPRING CENTRED			25
		<b>DH-0513</b>	SPRING CENTRED			25
		<b>DH-0514</b>	SPRING CENTRED			20