

TH7 Hydraulic Hose - SAE 100R7

Black Thermoplastic

Recommended For: Petroleum, water base and synthetic hydraulic fluids. Applications include: power and telephone mobile equipment (cherry pickers), lubrication lines, blowout preventer control lines, hydraulic lifts and farm and construction machinery.

Standards: Meets or exceeds performance requirements of SAE 100R7 with a significantly tighter bend radius.

Tube: 100% seamless Nylon - Type Z that easily handles a broad range of hydraulic fluids, including phosphate esters and water glycol.

See Characteristics Of Hose Stock Types.

Reinforcement: Synthetic fibre.

Cover: Black urethane resists hydraulic fluids, high temperatures, aging and weathering. Black TH7 cover is perforated for use in general hydraulic and pneumatic service.

See Characteristics Of Hose Stock Types.

Temperature Range: -65°F to +200°F (-54°C to +93°C) continuous service for petroleum and synthetic oils. Maximum of +158°F (+70°C) for water, water/oil emulsions and water glycol.

Couplings Recommendation: (see Southcott Crimp Data Book/Charts)

Gates MegaCrimp® (G) Couplings (-4 through -16)

Swage (PCTS) Couplings (-2 and -3 only)

Child Super Crimp (S) Series Couplings (-4, -6 and -8 only)

Refer www.southcott.com.au for current crimp specifications.

Hose Specifications

Part Number	Θ			Q		Ø		Q		(P)		Length (m)
Standard	Dash	Inch	DN	Inch	mm	PSI	Bar	PSI	Bar	Inch	mm	Reel
2TH7	2	1/8	3	0.32	8.1	3,000	207	12,000	828	0.5	13	76
3TH7	3	3/16	5	0.41	10.4	3,000	207	12,000	828	0.8	20	76
4TH7	4	1/4	6	0.50	12.7	2,750	190	11,000	759	1.5	38	76
5TH7	5	5/16	8	0.56	14.2	2,500	172	10,000	689	2.3	57	76
6TH7	6	3/8	10	0.64	16.3	2,250	155	9,000	621	2.8	70	76
8TH7	8	1/2	12	0.80	20.3	2,000	138	8,000	552	3.8	95	76
12TH7	12	3/4	19	1.05	26.7	1,250	86	5,000	345	5.0	127	60
16TH7	16	1	25	1.32	33.6	1,000	69	4,000	276	10.0	254	60

Additional Product

HoseType Couplings and Ferrules				Associated Protective Product							
Standard			nild Series	Wire Spring	Spiral	Heat	Tex-	Shrink Band	Life	Life Guard	
	Series	Coupling	Ferrule	Guard	Guard	Guard	Sleeve	Clamps	Guard	Collar	
2TH7	2PCTS	-	-	HSG-01	SGX12	HTG-09	TEXS17	SB15	14LG5K	6SC4	
3TH7	3PCTS	-	-	HSG-01	SGX16	HTG-11	TEXS17	SB15	14LG5K	6SC4	
4TH7	4G	S	FSP-204	HSG-02	SGX16	HTG-13	TEXS17	SB15	14LG5K	6SC4	
5TH7	5G	-	-	HSG-03	SGX16	HTG-14	TEXS20	SB22	14LG5K	6SC4	
6TH7	6G	S	FSP-206A	HSG-03	SGX16	HTG-20	TEXS23	SB22	16LG4K	6SC4	
8TH7	8G	S	FSP-208	HSG-05	SGX20	HTG-26	TEXS27	SB25	20LG4K	8SC4	
12TH7	12G	-	-	HSG-08	SGX25	HTG-30	TEXS40	SB34	26LG3K	12SC4	
16TH7	16G	-	-	HSG-11	SGX40	HTG-34	TEXS44	SB41	32LG3K	16SC4	

