## **TH7NCDL Non-Conductive Hydraulic Hose SAE 100R7**



## **Orange Thermoplastic**

**Recommended For:** Petroleum and synthetic hydraulic fluids. Applications include: power and telephone mobile equipment (cherry pickers), lubrication lines, blowout preventer control lines, hydraulic lifts and farm and construction machinery. **Standards:** Meets SAE 100R7 non-conductivity requirements and meets or exceeds performance requirements of SAE 100R7 with a significantly tighter bend radius. Meets ANSI A92.2 for vehicle mounted aerial devices (-4 to -8).



**Tube:** 100% seamless Nylon - Type Z that easily handles a broad range of hydraulic fluids, including phosphate esters and water glycol (-2, -12 and -16), or Polyester (-3 through -8).

See Characteristics Of Hose Stock Types.

Reinforcement: Synthetic fibre (except -2).

**Cover:** Orange urethane resists hydraulic fluids, high temperatures, aging and weathering. Orange TH7NCDL cover is non-perforated for applications requiring electrical non-conductivity.

See Characteristics Of Hose Stock Types.

**Temperature Range:** -65°F to +200°F (-54°C to +93°C) continuous service for petroleum and synthetic oils. Maximum of +158°F (+70°C) for water, water/oil emulsions and water glycol.

Couplings Recommendation: (see Southcott Crimp Data Book/Charts)

Gates MegaCrimp® (G) Couplings (-4 through -16)

Swage (PCTS) Couplings (-2 and -3 only)

Child Super Crimp (S) Series Couplings (-4, -6 and -8 only)

Refer www.southcott.com.au for current crimp specifications.

## **Hose Specifications**

Part Number	$\Theta$			<u>O</u>		0		Ŏ.		(P.		Length (m)
Standard	Dash	Inch	DN	Inch	mm	PSI	Bar	PSI	Bar	Inch	mm	Reel
4TH7NCDL	4	1/4	6	0.50	12.7	2,750	190	11,000	759	1.5	38	76
6TH7NCDL	6	3/8	10	0.64	16.3	2,250	155	9,000	621	2.8	70	76
8TH7NCDL	8	1/2	12	0.80	20.3	2,000	138	8,000	552	3.8	95	76

## **Additional Product**

HoseType	Coupl	ings and F	errules	Associated Protective Product						
	Gates Child 1 Piece 2 Piece Series		nild	Heat	Tex-	Shrink Band	Life Guard	Life Guard Collar		
Standard			e Series	Guard	Sleeve					
	Series	Coupling Ferrule		Guaru	Sieeve	Clamps	Guaru			
4TH7NCDL	4G	S	FSP-204	HTG-22	TEXS31	SB41	26LG3K	-		
6TH7NCDL	6G	S	FSP-206A	HTG-30	TEXS36	SB48	32LG3K	-		
8TH7NCDL	8G	S	FSP-208	HTG-36	TEXS44	SB54	-	-		