

Terminator[®] Air & Multi Purpose Hose

*NOTE: being superseded by "Plant Master Xtreme 501 AR"

Specification: 3202T/3202TW, Non-Conductive at 1,000V DC

Recommended For: Terminator is one tough hose with a rugged cover for ouotstanding abrasion resistance and extended service life where constant flexing and bending is required. This top of the line premium oil resistant hose is designed for applications involving air, oil and water, as well as grease sprays, paraffin waxes, salt solutions and a variety of chemicals. It offers excellent durability for extra long life in mining, air drill, construction, poultry plant abbatoirs, quarries, shipyards, food processing, railroads and other severe service environments.

Tube: Nitrile - Type C. Black. RMA (Class A) high oil resistance.
See Characteristics Of Hose Stock Types.
Reinforcement: Synthetic, high tensile textile cord.
Cover: Carboxylated Nitrile - Type C4. Yellow.
See Characteristics Of Hose Stock Types.
Temperature Range: -40°F to +212°F (-40°C to +100°C) continuous service

Couplings Recommendation: (see Southcott Crimp Data Book/Charts)

Gates MegaCrimp (G) Couplings (-4 to -20) Gates Low Pressure (GLX) Couplings (-4 to -20) Gates GlobalSpiral Plus (GSP) Couplings (-24 & -32) Refer www.southcott.com.au for current crimp specifications.

Hose Specifications

Part Number	Θ		<u>I</u> O		Ø		Suction				Length (m)	
Standard	Dash	Inch	DN	Inch	mm	PSI	Bar	in Hg	mm Hg	Inch	mm	Reel
04TERMINATOR	4	1/4	6	0.57	14.5	501	35	30	762	3.0	76	183
06TERMINATOR	6	3/8	10	0.75	19.0	501	35	25	635	3.0	76	183
08TERMINATOR	8	1/2	12	0.89	22.6	501	35	25	635	5.0	127	183
12TERMINATOR	12	3/4	19	1.22	31.0	501	35	15	381	6.0	152	183
16TERMINATOR	16	1	25	1.51	38.4	501	35	10	254	7.9	201	107
20TERMINATOR	20	1-1/4	31	1.78	45.2	501	35	10	254	10.0	254	107
24TERMINATOR	24	1-1/2	38	2.09	53.1	501	35	10	254	12.0	305	30
32TERMINATOR	32	2	51	2.64	67.1	501	35	10	254	14.0	356	30

Additional Product

Hose Type	Couplings and Ferrules		Associated Protective Product						
Standard	Gates 1- & 2-piece Series Coupling Ferrule		Wire Spring Guard	Spiral Guard	Heat Guard	Tex- Sleeve	Shrink Band Clamps		
04TERMINATOR		GLX	HSG-02	SGX16	HTG-13	TEXS17	SB19		
06TERMINATOR	G or	GLX	HSG-03	SGX20	HTG-18	TEXS20	SB22		
08TERMINATOR	G or GLX		HSG-06	SGX25	HTG-20	TEXS27	SB25		
12TERMINATOR	G or GLX		HSG-10	SGX32	HTG-26	TEXS36	SB34		
16TERMINATOR	G or GLX		HSG-12	SGX40	HTG-30	TEXS44	SB48		
20TERMINATOR	G or GLX		HSG-13	SGX50	HTG-34	TEXS53	SB54		
24TERMINATOR	GSP	24GSP1F-2	HSG-14	SGX50	HTG-40	TEXS66	SB60		
32TERMINATOR	GSP 32GSP1F-2		HSG-16	SGX75	HTG-56	TEXS85	SB73		



