




PRESSURE REDUCING VALVES





PRPS

	Pressure Reducing				Pressure Reducing / Relieving		
	Part Number	Flow L/min	Cavity		Part Number	Flow L/min	Cavity
	PRPS-10-N-S-0-15	46	1030		PRRS-08-N-S-0-15	23	0830
					PRRS-10-N-S-0-15	46	1030
					PRRS-12-N-S-0-30	91	1230

COUNTER BALANCE VALVES





CBPA

CBPS



	Standard 4:1				Sealed Piston 4:1		
	Part Number	Flow L/min	Cavity		Part Number	Flow L/min	Cavity
	CBPA-08-N-S-0-30	38	0825		CBPS-08-N-S-0-30	38	0825
	CBPA-10-N-S-0-30	76	1025		CBPS-10-N-S-0-30	76	1025
	CBPA-12-N-S-0-30	132	1225		CBPS-12-N-S-0-30	132	1225

CBPG

CBPA-20M (Also available in **CBPG-20M** & **CBPS-20M**)

	Vented Piston 4:1				As Standard to suit Sun Cavity 4:1		
	Part Number	Flow L/min	Cavity		Part Number	Flow L/min	Cavity
	CBPG-08-N-S-0-30	38	0825		CBPA-20M-N-S-0-15	76	T-11A
	CBPG-10-N-S-0-30	76	1025		CBPA-20M-N-S-0-30		
	CBPG-12-N-S-0-30	132	1225		CBPA-20M-N-S-0-50		

CBPP

	Standard 10:1		
	Part Number	Flow L/min	Cavity
	CBPP-10-N-S-0-10-30-C	60	1025
	CBPP-20M-N-S-0-10-30C		T-11A

NB: The above Cartridges available in the following pressure range - substitute the last 2 numbers.

15 = 50 to 1500 psi (3.5 to 103 bar)

30 = 100 to 3000 psi (7 to 206 bar)

40 = 600 to 4000 psi (28 to 275 bar) (Applicable only to size 12 counter-balance valves)

50 = 1500 to 5000 psi (103 to 345 bar) (NOT applicable to size 12 counter-balance valves)

For line mount bodies to suit the above cartridges refer to Section J.

Use the cavity size to select the correct body type then choose the desired port size.